

RUBBERWORX

PVC WATER SUCTION AND DISCHARGE



This light-duty water suction and discharge hose is designed for use in construction, dewatering, agricultural and industrial applications. PVC tube designed to handle residual chemicals in water transfer applications.

| | |
|----------------------------------|-----------------------------------|
| TUBE: | PVC |
| REINFORCEMENT: | WHITE PVC HELIX |
| COVER: | PVC |
| TEMPERATURE: | -23°F to 140°F |
| BRANDING: | PVC SUCTION AND DISCHARGE 100 PSI |
| PACKAGING SPECIFICATIONS: | 100' COILS AND 20' SECTIONS |

| SA # | ID (IN) | OD (IN) | WP (PSI) | BURST (PSI) | BEND RADIUS (IN) | VACUUM RATING (HG) | WEIGHT | PACKAGING |
|--------------|---------|---------|----------|-------------|------------------|--------------------|--------|-----------|
| 1002103-075 | 0.75 | 1.02 | 100 | 300 | 2 | 29 | 0.21 | 20', 100' |
| 1002103-100 | 1.00 | 1.29 | 100 | 300 | 3 | 29 | 0.29 | 20', 100' |
| 1002103-125 | 1.25 | 1.56 | 90 | 270 | 4 | 29 | 0.38 | 20', 100' |
| 1002103-150 | 1.50 | 1.84 | 90 | 270 | 4 | 29 | 0.49 | 20', 100' |
| 1002103-200 | 2.00 | 2.39 | 70 | 210 | 5 | 29 | 0.72 | 20', 100' |
| 1002103-250 | 2.50 | 2.92 | 65 | 195 | 7 | 29 | 0.99 | 20', 100' |
| 1002103-300 | 3.00 | 3.46 | 55 | 165 | 8 | 29 | 1.29 | 20', 100' |
| 1002103-400 | 4.00 | 4.56 | 50 | 150 | 12 | 29 | 2.05 | 20', 100' |
| 1002103-500 | 5.00 | 5.65 | 45 | 135 | 20 | 29 | 3.01 | 20', 100' |
| 1002103-600 | 6.00 | 6.80 | 45 | 135 | 23 | 29 | 4.45 | 20', 100' |
| 1002103-800 | 8.00 | 8.95 | 40 | 120 | 34 | 29 | 6.86 | 20', 100' |
| 1002103-1000 | 10.00 | 11.34 | 40 | 120 | 40 | 29 | 12.05 | 20', 100' |
| 1002103-1200 | 12.00 | 13.19 | 35 | 105 | 50 | 29 | 15.27 | 20', 100' |